

Transmittance

$U_w \geq 1.2$ (W/m²K)

Consult typology, dimensions and glass.

Acoustic insulation

Maximum glazing	Inner sash: 38 mm Outer sash: 22 mm
Minimum glazing	Inner sash: 13 mm Outer sash: 11 mm
Maximum acoustic insulation	Rw = 50 dB

Sightlines

Frame	122 mm
Sash	121 mm

Profile Thickness

Window	1.6 mm
--------	--------

Polyamide strip length

Frame	35 mm
Sash	20 mm

Maximum dimensions / Sash

Width (L) = 1,200 mm

Height (H) = 2,200 mm

Consult maximum weight and dimensions according to typologies.

Maximum weight / Sash 150 kg

Categories achieved at test centre

Protection against atmospheric agents.

Air permeability

(UNE-EN 12207): Class 4

Water tightness

(UNE-EN 12208): Class E1650

Wind resistance

(UNE-EN 12210): Class C5

* Reference test 1.23 x 1.48 m / 1 sash.

Test verified by

ALUMINIOS CORTIZO S.A.U.

Extrusion alloy

6063 T-5

Finishes

Possibility of dual colour.

Colour powder coating (RAL, mottled & rough).

According to Qualicoat >60 microns

Wood effect powder coating.

According to Qualideco standard

Anodised.

According to Ewwa Euras / Standard Class 15 / Optionally Class 20 and 25

Opening possibilities

Inward opening: 1 & 2 sash side hung and 1 & 2 sash tilt & turn.

